



Fleet Tracking *Simplicity*

Powered Trailer Tracker

24/7
Activation Hotline
920.338.0479

Step 1: Mounting

- A. Find an open location on the top, roadside of the trailer nose. Do not install curbside.
- B. **IMPORTANT:** Ensure the mounting location is over a metal rail either from the outside or inside of the trailer. Device should be mounted to the **OUTSIDE** of the trailer only.
- C. Mark the location for each of the mounting bolts. There should be two (2) bolts and two (2) locknuts included.
- D. Drill holes into the locations marked in the previous step.
- E. Install the 2 bolts through the mounting holes of the device.
- F. Securely fasten to the trailer using the provided locknuts.



Step 2: Power Connections

- A. **IMPORTANT:** Keep in mind that this device needs power to operate. The best placement of the power cable is running from the external device to the inside of the trailer and then to wherever designated and constant power is located.
- B. We advise ensuring that the cable is not loose or dangling in its final placement.
- C. The cabling **IS** weather-proof. If the interior of the trailer is unfit for cabling, the installer should run the cable along the outside of the trailer. Should this happen, flush and secure cabling is very important for the longevity of the product.
- D. The wires needed for power connectivity are **RED** (+) and **BLACK** (-).



Step 3: Verify the device is tracking

- A. Wait 5 minutes from the time the device is powered.
- B. Have the ESN number from the device available before contacting CyntrX.
- C. Email or call:
 - Email: activations@cyntrx.com
 - Call: (866) 312-3782